DECO[®] LIGHTING



Performance Data

CRI

80+

ССТ

3500K, 4000K, 5000K

Projected Lifetime

>54,000 Hours (L70); >51,000 Hours (L90)

Dimming

0-10V Dimming Standard. 100% down to 10%

Operating Temperature

-30°C to +55°C Ambient

UL Listed

UL, Suitable for dry and damp locations

Warrantv

5 year Standard 10 year Optional



Order #:

Description

Client:

Project Name:_

The revolutionary and highly efficient Game Over LED Latch & Close door frame retrofit kit features easy installation and offers a costsaving solution for upgrading fluorescent troffers or parabolics to LED technology. Ideal for commercial applications such as offices, classrooms, healthcare facilities, and retail spaces. The GO-LED Latch and Close retrofit kit features dimming standard and delivers the most advanced LED technology on the market with an efficacy of 140 lumens per watt. DLC Premium listed for enhanced utility rebates, the GO-LED Latch Kit provides a simpler, quicker solution than piece-style retrofit kits and can be installed in 3-5 minutes.

Features

- Temperswitch allows users to select between 5000K, 4000K, and 3500K in the field by simply switching an easily accessible three position switch. Fixture comes set/standard at 40K.
- High reflectance optical engine delivers main beam focus through the optically designed acrylic lens.
- Linear ribbed acrylic lens overlay balances efficiency & aesthetics.
- Reflector distributes light through both optical elements.
- Ideal for recessed commercial applications such as offices,

hospitals, and schools

- L70 Lifetime Rating: 122,000 Hours
- Ultra efficient 140 lumens per watt performance
- Accurate interior color rendering with 80+ CRI
- Architectural Narrow style diffuser lens provides smooth, even illumination
- Door Frame style retrofit kit enables quick and easy upgrade from dated fluorescent fixtures to modern LED performance

GO-LED	L1	1	354050	U		BT	L 1	L
A	B	C	D	•	F	G	6	0

Ordering Information

A	FIX	FURE	SERIES	
---	-----	------	--------	--

	GO- LED	0.00	me Over Latch Door Frame Kit
B	SIZE		
_	22		2 x 2
	24		2 x 4
C	WATTAGE/L (SIZE 22)	UMENS	
	24		24W/36001,2
	(SIZE 24)		
	32		32W/44801,2

D CCT	
354050	3500K-4000K-5000K
E VOLTAGE	
U	120-277V
FIXTURE TY	(PE
LC	Latch and Close Kit
G CONTROLS	;
BT	Bluetooth DECO Mesh™ ³
H OPTIONS	
E	Emergency Backup
WARRANTY	74
-	5 Year Warranty
10	10 Year Warranty
10L	10 Year Warranty including labor

¹ Delivered Lumens (3500K)

² DLC Premium


³1% Dimming when ordered with Bluetooth ⁴ 5 Year Warranty is Standard unless specified

Dimensions

	Length	Width	Depth
2 x 2	23.90	23.90	3.10
2 x 4	47.90	23.90	3.10


Photometrics

Model - 2x2 25W 4000K



Zone	Lumens	%Lamp	%Luminaire
0-30	807.1	27.1%	27.1%
0-40	1,310.0	44%	44%
0-60	2,291.3	76.9%	76.9%
50-90	670.5	22.5%	22.5%
70-100	303.7	10.2%	10.2%
90-120	7.0	0.2%	0.2%
0-90	2,961.8	99.4%	99.4%
90-180	17.7	0.6%	0.6%
0-180	2,979.5	100%	100%

Polar Graph - 2x4 35W 4000K



Lens Detail



© Copyright Deco Lighting, Inc. 2018 2917 Vail Ave. Commerce Ca 90040 www.getdeco.com info@getdeco.com t: (800) 613-DECO f: (310)366-6855 Deco Lighting practices a program of continuous product development, and as a result product specifications change frequently. We reserve the right to change product specifications without notice. Contact Deco for the latest product information.



Zonal Lumen Summary

Zonal Lumen Summary

Zone	Lumens	%Lamp	%Luminaire
0-30	1,112.8	26.8%	26.8%
0-40	1,808.7	43.5%	43.5%
0-60	3,174.3	76.4%	76.4%
50-90	956.0	23%	23%
70-100	441.4	10.6%	10.6%
90-120	10.5	0.3%	0.3%
0-90	4,130.3	99.4%	99.4%
90-180	25.2	0.6%	0.6%
0-180	4,155.5	100%	100%