




VECTOR 2 SURFACE/RECESSED FLANGELESS

Client: _____ Order #: _____
Project Name: _____ Type: _____ Qty: _____

Ambient Linear LED
Performance Data

DECOMESH™



Drop Lens 1/2" or 2" (Direct)

Louver (Direct)



CRI
95 min with R9 of 69 or better

CCT
2700K, 3000K, 3500K, 4000K,
5 Channel Color Tuning

Projected Lifetime
240,000 Hours (L80);
110,000 Hours (L90)

Dimming
0-10V dimming standard

Operating Temperature
-30°C to +55°C (-22°F to +131°F)

ETL Listed
Approved for dry and damp
locations

Warranty
5 year Standard
10 year Optional

Description

The Vector 2 is a 27/16" wide linear architectural luminaire. While the Vector has a slim and discreet profile, it provides excellent illumination for offices, laboratories, libraries, and commercial spaces. Vector is available in standard lengths of 2', 3', 4', 6', and 8', and can be joined together in seamless runs of any length in 1 foot increments.

Features


PERFORMANCE

- Selected by IES for the 2017 Progress Report
- Up to 1200 lm/ft direct at 4000K

PHYSICAL

- Profile Dimensions: 2.96" wide x 4.6" high
- End Caps: Die cast aluminum with powder coat finish
- Housing: Extruded Aluminum with powder coat finish

- Direct Lens: Extruded Satin Acrylic
- Light Engine: Aluminum core LED board mounted to a white extruded chassis with integral driver and quick electrical disconnects for rapid tool-less servicing
- Weight: 30 pounds (8ft luminaire)



Ordering Information

A FIXTURE SERIES

V2S Vector 2 Surface

B LENGTH

2	2'
3	3'
4	4'
6	6'
8	8'
Sxxx	System ¹

C OUTPUT

L	6W/ft ^{7,8}
M	9W/ft ⁷
H	12W/ft

D CCT

27	2700K
30	3000K
35	3500K
40	4000K

E DIRECT LENS

—	Frosted ⁵
C	1/2" Drop Lens
D	2" Drop Lens
L	Louver

F VOLTAGE

U	120-277V
---	----------

G FINISH⁴

W	Textured White
S	Textured Silver
B	Textured Black
##	Specialized Colors ^{2,3}
C	Textured Custom Colors
AM	Antimicrobial Paint Finish

H OPTIONS

E	Emergency Battery Backup
---	--------------------------

I CONTROLS

BT Bluetooth DECO Mesh™⁶

J WARRANTY⁹

-	5 Year Warranty
10	10 Year Warranty
10L	10 Year Warranty including labor

¹Replace "xxx" with desired system length, in feet. See Continuous Run Guide for additional information (separate document)

²See below for Ordering Codes on 24 Specialized Finishes. Example "07"

³Please Note: All orders under 25 linear feet will require a one-time set up charge. Please consult factory for charge.

⁴All finishes are textured unless specified otherwise by the customer

⁵See Page 6 for more information


⁶1% Dimming when ordered with Bluetooth

⁷Not Available for 2' Direct Fixture

⁸Not Available for 3' Direct Fixture

⁹5 Year Warranty is Standard unless specified

Dimensions



	2	3	4	6	8
X ₁	24.91"	36.91"	48.91"	72.91"	96.91"

Specialized Colors

A-Classic

01	Natural Aluminum	RAL #7035
02	Silver Bullet	RAL #7038
03	Raven	RAL #9005
04	Crystal White	RAL #9010
05	Macademia	RAL #9003
06	Hampden	RAL #9001
07	London	RAL #7044

B-Urban

08	Urban Native	RAL #8025
09	Military Green	RAL #6011
10	Carmin	RAL #8028
11	Chocolate Spice	RAL #8017
12	Asher Grey	RAL #7004
13	Tech Grey	RAL #7016
14	Slate	RAL #7031
15	Mason	RAL #7039


C-Fresh

16	Violet Dreams	RAL #4006
17	Sangria Sunset	RAL #2004
18	Deep Pink	RAL #4010
19	Ruby Red	RAL #3027
20	Island Skye	RAL #6027
21	Sophia	RAL #5015
22	Antique Spring	RAL #6019
23	Daisy	RAL #1018
24	Gun Metal	RAL #7024

Please Note: All orders under 25 linear feet will require a one-time set up charge. Please consult factory for charge.

Photometrics

Polar Graph - 4' High Output 4000K



Delivered Lumens: 4640
CRI: 97


Direct (Down) Lumen Chart:

OUTPUT SELECTION	LOW	MEDIUM	HIGH
NOMINAL WATTAGE	6W/ft	9W/ft	12W/ft
LUMENS PER FOOT	456	855	928
2' LENGTH			
System Wattage	12.00	18.00	24.00
Lumen Output	912	1700	1856
3' LENGTH			
System Wattage	18.00	27.00	36.00
Lumen Output	1368	2550	2784
4' LENGTH			
System Wattage	24.00	36.00	48.00
Lumen Output	1824	3400	3700
6' LENGTH			
System Wattage	36.00	54.00	72.00
Lumen Output	2736	5100	5568
8' LENGTH			
System Wattage	48.00	72.00	96.00
Lumen Output	3648	6800	7400

Lumen values shown are for 4000K models. For other color temperatures, use the below multipliers:
2700K: 0.85, 3000K: 0.90, 3500K: 0.95


Continuous Runs

When a system run is ordered, individual sections are shipped, labeled with their Section of Run noted at the end of the part number. Shown below is an example of a 13' continuous run. For more information, refer to the continuous run guide.



Lens Accessories


Drop Lens (Direct)
Available in 1/2" and 2"



A white frosted PMMA lens that protrudes from the luminaire housing by 0.5" or 1.5". End caps are chemically welded to the lens.



Louver (Direct)



A Semi-specular parabolic louver. 22 GA. Aluminum Louver depth 3/4" louver spacing 2". Provides excellent glare control.

