



# VECTOR 2 RECESSED T-BAR

Ambient Linear LED

## Performance Data

### CRI

95 min with R9 of 69 or better

### CCT

2700K, 3000K, 3500K, 4000K,  
5 Channel Color Tuning

### Projected Lifetime

240,000 Hours (L80);  
110,000 Hours (L90)

### Dimming

0-10V dimming standard

### Operating Temperature

-30°C to +55°C (-22°F to +131°F)

### ETL Listed

Approved for dry and damp  
locations


### Warranty

5 year Standard  
10 year Optional


Client: \_\_\_\_\_  
Project Name: \_\_\_\_\_

Order #: \_\_\_\_\_  
Type: \_\_\_\_\_ Qty: \_\_\_\_\_


DECO MESH™



Louver (Direct)



Drop Lens 1/2" or 2" (Direct)



## Description

The Vector 2 is a 27/16" wide linear architectural luminaire. While the Vector has a slim and discreet profile, it provides excellent illumination for offices, laboratories, libraries, and commercial spaces. Vector is available in standard lengths of 2', 3', 4', 6', and 8', and can be joined together in seamless runs of any length in 1 foot increments.

## Features

### PERFORMANCE

- Selected by IES for the 2017 Progress Report
- Up to 1200 lm/ft direct at 4000K

### PHYSICAL

- Profile Dimensions: 2.95" wide x 4.6" high
- End Caps: Die cast aluminum with powder coat finish
- Housing: Extruded Aluminum with powder coat finish

- Direct Lens: Extruded Satin Acrylic
- Light Engine: Aluminum core LED board mounted to a white extruded chassis with integral driver and quick electrical disconnects for rapid tool-less servicing
- Weight: 30 pounds (8ft luminaire)

**V2T**

**U**

**BT**

A

B

C

D

E

F

G

H

I

J

K

## Ordering Information

### A FIXTURE SERIES

V2T Vector 2 Recessed T-Bar

### B STYLE

1	15/16 T-Bar
2	9/16 T-Bar
3	Screw Slot T-Bar

### C LENGTH

2	2'
4	4'
6	6'
8	8'

### D OUTPUT

L	6W/ft <sup>7,8</sup>
M	9W/ft <sup>7</sup>
H	12W/ft

### E CCT

27	2700K
30	3000K
35	3500K
40	4000K

### F DIRECT LENS<sup>5</sup>

	Frosted <sup>4</sup>
C	1/2" Drop Lens
D	2" Drop Lens
L	Louver

### G VOLTAGE

U	120-277V
---	----------

### H FINISH<sup>9</sup>

W	Textured White
S	Textured Silver
B	Textured Black
##	Specialized Colors <sup>1,2</sup>
C	Textured Custom Colors

### I OPTIONS

E	Emergency Battery Backup
---	--------------------------

### J CONTROLS


BT Bluetooth DECO Mesh™<sup>6</sup>

### K WARRANTY<sup>9</sup>

-	5 Year Warranty
10	10 Year Warranty
10L	10 Year Warranty including labor

- <sup>1</sup> See below for Ordering Codes on 24 Specialized Finishes. Example "07"
- <sup>2</sup> Please Note: All orders under 25 linear feet will require a one-time set up charge. Please consult factory for charge.
- <sup>3</sup> All finishes are textured unless specified otherwise by the customer
- <sup>4</sup> Fixture standard
- <sup>5</sup> See page 3 for more information
- <sup>6</sup> 1% Dimming when ordered with Bluetooth
- <sup>7</sup> Not Available for 2' Direct Fixture
- <sup>8</sup> Not Available for 3' Direct Fixture
- <sup>9</sup> 5 Year Warranty is Standard unless specified

**Dimensions**



	2	3	4	6	8
<b>X<sub>1</sub></b>	23.7"	35.7"	47.7"	71.7"	95.7"
<b>X<sub>2</sub></b>	23"	35"	47"	71"	95"

**Specialized Colors**

**A-Classic**

	01	Natural Aluminum	RAL #7035
	02	Silver Bullet	RAL #7038
	03	Raven	RAL #9005
	04	Crystal White	RAL #9010
	05	Macademia	RAL #9003
	06	Hampden	RAL #9001
	07	London	RAL #7044

**B-Urban**

	08	Urban Native	RAL #8025
	09	Military Green	RAL #6011
	10	Carmin	RAL #8028
	11	Chocolate Spice	RAL #8017
	12	Asher Grey	RAL #7004
	13	Tech Grey	RAL #7016
	14	Slate	RAL #7031
	15	Mason	RAL #7039


**C-Fresh**

	16	Violet Dreams	RAL #4006
	17	Sangria Sunset	RAL #2004
	18	Deep Pink	RAL #4010
	19	Ruby Red	RAL #3027
	20	Island Skye	RAL #6027
	21	Sophia	RAL #5015
	22	Antique Spring	RAL #6019
	23	Daisy	RAL #1018
	24	Gun Metal	RAL #7024

Please Note: All orders under 25 linear feet will require a one-time set up charge. Please consult factory for charge.

**Photometrics**

Polar Graph - 4' High Output 4000K



Delivered Lumens: 4640  
CRI: 97


**Direct (Down) Lumen Chart:**

OUTPUT SELECTION	LOW	MEDIUM	HIGH
NOMINAL WATTAGE	6W/ft	9W/ft	12W/ft
LUMENS PER FOOT	456	855	928
<b>2' LENGTH</b>			
System Wattage	12.00	18.00	24.00
Lumen Output	912	1700	1856
<b>3' LENGTH</b>			
System Wattage	18.00	27.00	36.00
Lumen Output	1368	2550	2784
<b>4' LENGTH</b>			
System Wattage	24.00	36.00	48.00
Lumen Output	1824	3400	3700
<b>6' LENGTH</b>			
System Wattage	36.00	54.00	72.00
Lumen Output	2736	5100	5568
<b>8' LENGTH</b>			
System Wattage	48.00	72.00	96.00
Lumen Output	3648	6800	7400

Lumen values shown are for 4000K models. For other color temperatures, use the below multipliers:  
2700K: 0.85, 3000K: 0.90, 3500K: 0.95


**Lens Accessories**

Drop Lens (Direct)  
Available in 1/2" and 2"



A white frosted PMMA lens that protrudes from the luminaire housing by 0.5" or 1.5". End caps are chemically welded to the lens.

Louver (Direct)



A Semi-specular parabolic louver. 22 GA. Aluminum Louver depth 3/4" louver spacing 2". Provides excellent glare control.